









Earthsafe / GenApp Fuel Systems For Generator Dealers

Earthsafe has designed new fuel system monitors, equipment and controls to meet the challenges of generator dealers. The system offers low cost devices for generator sub-base fuel tanks, and for more complex systems interior to buildings. Modbus or BACnet connectivity is built-in

<p>M1: Simplex Transfer Pumps (2.5, 5.0, 10.0 GPM) Supply or Return Simplex Fuel Pump for Generator Fuel Supply or Return Flow. Open Frame or Enclosure Mounting. Integral Controls accept tank level sensors 1-4 point.</p>	
<p>M2: Duplex Transfer Pumps (2.5, 5.0, 10.0 GPM) Simplex Fuel Pump for Generator Fuel Supply or Return Flow. Open Frame or Enclosure Mounting. Integral Controls accept tank level sensors 1-4 point. Unit can serve fuel feeds to multiple generator tanks.</p>	
<p>M3: Filter Polishers (2.5, 5.0, 10.0 GPM) AXI Feature Set Positive displacement pump, magnetic conditioner, centrifugal filter separator, final 1 micron dirt and water. Open Frame or Enclosure Mount. Programmable controller with display, cycle time settings, pump run hour meter.</p>	
<p>M4: Remote Tank Fill Station Fill Station for delivery by pump equipped truck. Controller monitors high level sensor for 85-90-95% points with audible and visual alarms. Actuated Shutoff Valve. Optional analog sensor and display for tank gallons, fuel height, and % full.</p>	
<p>M4P: Tank Fill Station with Pump to Rooftop (25 GPM) Fill Station for rooftop or remote generator tanks. Pump is positive displacement with motor match to pressure requirements up to 50 story building. Controller monitors high level sensor for 85-90-95% points with audible and visual alarms. Optional analog.</p>	
<p>M5gt: Sub-Base or Day Tank Refill Control with Optional Return Pump Gen Tank Re-Fill System. Open frame or Enclosure Mount. Controller monitors 4-5 point level sensor in tank for refill start and stop with high and low alarms. Includes inlet solenoid valve for flow control and optional return flow pump.</p>	
<p>M5dt: Day Tank UL142 Cubic with Containment Compact Day Tanks with Containment. Controls and Accessories for Reliable Refill by Remote Pumps. Optional On-Board Simplex or Duplex Suction Pumps. Optional Return Flow Pump.</p>	
<p>M6: Cubic Storage Tanks UL142 Double Wall or UL 2085 Fire Rated (250-2500 GAL) Space Saving Cubic Fuel Storage Tank. UL 142 Steel Double Wall Tanks or UL 2085 Fire rated. Complete Accessories including vents, gauges, and special valves.</p>	
<p>C1-ATG: Gen Sub-Base Tank Level Gauge and Leak Detection The C1-ATG system is designed for sub-base tanks from 8 inch to 8 feet in depth. The graphic display includes fuel gallons, height, % full, and temperature. Audible and visual alarms. Output alarm relays and 4-20 mA analog output for level.</p>	