

# LM6S LUBE-WASTE OIL TANKS **earth safe**

Fuel Systems for Critical Power

## Cubic Steel Tanks for Lube and Waste Oil

**LM6.SSU Single Wall, Not-Insulated**

**LM6.SDU Double Wall, Not-Insulated**

**LM6.SDI Double Wall, Insulated**

- Cubic Steel Lube-Waste Oil Tanks
- Accessories: Vent Caps, Direct Read Gauge, Inspect Port, Fill, Suction Pipe and Return Fittings
- C1 Tank Monitor Panel with High, Low, Leak Alarm, Output Relays, 4-20mA Analog Transmitter and Leak Sensor

The LM6 Tank is a compact storage tank for oil used in and around generators enclosures. The tank system can be equipped with pumps and controls to provide a complete oil supply system for generators.



<b>Tank Specification</b>	Coated Steel Cubic Tank
<b>Controller</b>	C1 Control Panel
<b>Power</b>	120-230 VAC, 1P, 50-60 Hz
<b>Interface</b>	Power ON Light Analog Level Display Alarm Light Hi-Lo-Leak Modbus to BMS
<b>Standard Accessories</b>	Vent Caps Level Indicator Gauge Port Analog Level Leak Sensor
<b>Optional Accessories</b>	Tank Insulation Tank Heater

Model	GAL	WxLxH IN	Liter	W.L.H CM
LM6.25	25	12x24x24	100	30.60.60
LM6.50	50	12x36x36	200	30.90.90
LM6.75	75	12x30x36	300	60.76.90
LM6.100	100	30x30x36	400	76.76.90
LM6.250	250	30x48x48	1000	75.120.120
LM6.500	500	42x60x54	2000	110.150.140
LM6.750	750	48x72x54	3000	120.180.140
LM6.1000	1000	48x90x60	4000	120.230.150

**Add 2 IN (50) to each Dimension for Double Wall**

### Other Equipment

- LM1 Simplex DEF Transfer Pumps
- LM2 Duplex DEF Transfer Pumps
- LM4 DEF Tank Fill System
- Temperature Sensors and Control