



## Cubic Polyethelene (HDPE) Tanks for Generator DEF Systems

**UM5.PSU Single Wall, Not-Insulated**

**UM5.PDU Double Wall, Not-Insulated**

**UM5.PDI Double Wall, Insulated**

- Cubic HD Polyethelene DEF Tanks
- Accessories: Vent Caps, Direct Read Gauge, Inspect Port, Fill, Suction Pipe and Return Fittings
- C1 Tank Monitor Panel with High, Low, Leak Alarm, Output Relays, 4-20mA Analog Transmitter and Leak Sensor

The UM5 Tank is a compact storage tank for DEF used in and around generator enclosures. The tank system can be equipped with pumps and controls to provide a complete DEF supply system for generator SCR emissions control.



<b>Tank Specification</b>	HD Polyethelene Cubic Tank
<b>Controller</b>	C1 Control Panel
<b>Power</b>	120-230 VAC, 1P, 50-60 Hz
<b>Interface</b>	Power ON Light Alarm Light Hi-Lo-Leak
<b>Standard Accessories</b>	Vent Caps Level Indicator Fill-Gauge Port Analog Level Leak Sensor for DW
<b>Optional Accessories</b>	Double Wall Tank Insulation

Model	GAL	WxLxH IN	Liter	W.L.H CM
UM6.25	25	12x24x24	100	30.60.60
UM6.50	50	12x36x36	200	30.90.90
UM6.75	75	12x30x36	300	60.76.90
UM6.100	100	30x30x36	400	76.76.90

**Add 2 IN (50) to each Dimension for Double Wall**

### Other Equipment

- UM1 Simplex DEF Transfer Pumps
- UM2 Duplex DEF Transfer Pumps
- UM4 DEF Tank Remote Fill Station
- UM6.CHT Circulation Type Heater