


UM6cu

UM6cu:

Underground Cylindrical Stainless Steel Tank for DEF Urea – Single Wall or Double Wall with HDPE Exterior Coating

- Cylindrical Stainless Steel DEF Tanks with HDPE Exterior Coating. Optional Double Wall Containment
- Accessories: Vent Caps, Direct Read Gauge, Inspect Port, Fill, Suction Pipe and Return Fittings
- C1 Tank Monitor Panel with High, Low, Leak Alarm, Output Relays, 4-20mA Analog Transmitter and Leak Sensor



| | |
|------------------------------------|---------------------------------------------------------------------------------------|
| Tank Specification | Stainless Steel Cylindrical SW or DW Tank |
| Controller | C1 Control Panel |
| Power | 120 VAC, 1P, 50-60 Hz |
| Interface | Power ON Light Analog Level Display Alarm Light Hi-Lo-Leak Modbus to BMS |
| Output Relays (Dry Contact) | High and Low Level Leak Alarm Common Alarm |
| Standard Accessories | Vent Caps, Level Indicator, Gauge Port, Analog Level and Leak Sensor, Temp Sensors |
| Enclosure | Stainless Steel Construction HDPE Exterior Coating DW - Tank Containment |

| Model | GAL | DIAM IN | LENGTH IN | EMPTY WT LBS |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|-----------|--------------|
| UM6cu.1000 | 1000 | 64 | 72 | 1500 |
| UM6cu.1500 | 1500 | 64 | 108 | 2000 |
| UM6cu.2000 | 2000 | 64 | 144 | 2500 |
| UM6cu.2500 | 2500 | 64 | 180 | 3000 |
| UM6cu.3000 | 3000 | 64 | 216 | 3500 |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| Other Equipment | | | | |
| Other Equipment | UM1 Simplex DEF Transfer Pumps UM2 Duplex DEF Transfer Pumps UM4 DEF Tank Fill System UM5 DEF Day Tanks Temperature Sensors and Control Containment Sump Manhole Frame Cover Hold-Down Straps and Turnbuckle | | | |