

GEN DEF UM6P



Cubic Polyethelene (HDPE) Tanks for Generator DEF Systems

UM6.PSU Single Wall, Not-Insulated

UM6.PDU Double Wall, Not-Insulated

UM6.PDI Double Wall, Insulated

- Cubic HD Polyethelene DEF Tanks
- Accessories: Vent Caps, Direct Read Gauge, Inspect Port, Fill, Suction Pipe and Return Fittings
- C1 Tank Monitor Panel with High, Low, Leak Alarm, Output Relays, 4-20mA Analog Transmitter and Leak Sensor

The UM6 Tank is a compact storage tank for DEF used in and around generators enclosures. The tank system can be equipped with pumps and controls to provide a complete DEF supply system for generator SCR emissions control.



Tank Specification	HD Polyethelene Cubic Tank
Controller	C1 Control Panel
Power	120-230 VAC, 1P, 50-60 Hz
Interface	Power ON Light Alarm Light Hi-Lo-Leak
Standard Accessories	Vent Caps Level Indicator Fill-Gauge Port Analog Level Leak Sensor for DW
Optional Accessories	Double Wall Tank Insulation

Model	GAL	WxLxH IN	Liter	W.L.H CM
UM6.25	25	12x24x24	100	30.60.60
UM6.50	50	12x36x36	200	30.90.90
UM6.75	75	12x30x36	300	60.76.90
UM6.100	100	30x30x36	400	76.76.90
UM6.250	250	30x48x48	1000	75.120.120
UM6.500	500	42x60x54	2000	110.150.140
UM6.750	750	48x72x54	3000	120.180.140
UM6.1000	1000	48x90x60	4000	120.230.150

Add 2 IN (50) to each Dimension for Double Wall

Other Equipment

- UM1 Simplex DEF Transfer Pumps
- UM2 Duplex DEF Transfer Pumps
- UM4 DEF Tank Remote Fill Station
- UM5.RES DEF Reservoir Refill
- UM6.CHT Circulation Type Heater