



## Cubic Stainless Steel Tanks for DEF

**UM6.SSU Single Wall, Not-Insulated**

**UM6.SDU Double Wall, Not-Insulated**

**UM6.SDI Double Wall, Insulated**

- Cubic Stainless Steel DEF Tanks
- Accessories: Vent Caps, Direct Read Gauge, Inspect Port, Fill, Suction Pipe and Return Fittings
- C1 Tank Monitor Panel with High, Low, Leak Alarm, Output Relays, 4-20mA Analog Transmitter and Leak Sensor

The UM6 Tank is a compact storage tank for DEF used in and around generator enclosures. The tank system can be equipped with pumps and controls to provide a complete DEF supply system for generator SCR emissions control.



<b>Tank Specification</b>	Stainless Steel Cubic Tank
<b>Controller</b>	C1 Control Panel
<b>Power</b>	120-230 VAC, 1P, 50-60 Hz
<b>Interface</b>	Power ON Light Analog Level Display Alarm Light Hi-Lo-Leak Modbus to BMS
<b>Standard Accessories</b>	Vent Caps Level Indicator Gauge Port Analog Level Leak Sensor
<b>Optional Accessories</b>	Tank Insulation Tank Heater

Model	GAL	WxLxH IN	Liter	W.L.H CM
UM6.25	25	12x24x24	100	30.60.60
UM6.50	50	12x36x36	200	30.90.90
UM6.75	75	12x30x36	300	60.76.90
UM6.100	100	30x30x36	400	76.76.90
UM6.250	250	30x48x48	1000	75.120.120
UM6.500	500	42x60x54	2000	110.150.140
UM6.750	750	48x72x54	3000	120.180.140
UM6.1000	1000	48x90x60	4000	120.230.150

**Add 2 IN (50) to each Dimension for Double Wall**

### Other Equipment

- UM1 Simplex DEF Transfer Pumps
- UM2 Duplex DEF Transfer Pumps
- UM4 DEF Tank Fill System
- UM5 DEF Day Tanks
- Temperature Sensors and Control